

# Material Safety Data Sheet

MSDS No.: AHP1703  
Variant: U.S.A.-EN  
Version No: 1.3  
Validation Date: 03/22/2019

## Essentials S3 Core Filled Votive Candles

### SECTION 1: IDENTIFICATION

---

**Product Name:** Essentials S3 Core Filled Votive Candles

**Product Number:** 30243789

**Internal ID:** N/A

**Chemical Family:** N/A

**CAS Number:** N/A

**Chemical Name:** N/A

**Company**

Aromasong Home Products Co.,LTD  
5th Floor, Building 10, No.69 Gongyi Road,Nanqiao Town,Fengxian District,Shanghai,China,201401

**Manufacture**

Aromasong Home Products Co.,LTD  
5th Floor, Building 10, No.69 Gongyi  
Road,Nanqiao District.Shanghai  
China

**Business Contact**

Customer Service 03451 656 565  
Dunelm (Soft Furnishings) Ltd

### SECTION 2: HAZARD IDENTIFICATION

---

**Emergency Overview**

This material is NOT HAZARDOUS by OSHA Hazard Communication definition.


**Signal Word**

CAUTION.

**Hazards**

Slight eye irritant. Slight skin irritant.

NFPA®



HMIS®

Health		0
Flammability		1
Physical Hazard		0

**Physical State**

Slightly viscous liquid.

**Color**

Clear, colorless.

## Material Safety Data Sheet

MSDS No.: AHP1703  
Variant: U.S.A.-EN  
Version No: 1.3  
Validation Date: 03/22/2019

# Essentials S3 Core Filled Votive Candles

### Odor

Aroma Smell

### Odor Threshold

No value available.

### Potential Health Effects

#### Routes of Exposure

Eye. Skin. Inhalation. Ingestion.

#### Signs and Symptoms of Acute Exposure

See component summary.

Slight eye irritant. May be irritating to the skin.

#### Skin

May produce skin irritation. Not expected to be a skin absorption hazard.

#### Inhalation

Not expected to be an inhalation hazard.

#### Eye

May cause minor eye irritation.

#### Ingestion

Ingestion of high doses may cause discomfort and irritation of the gastrointestinal tract and CNS depression (fatigue, dizziness and possibly loss of concentration, with collapse, coma and death in cases of severe over-exposure).

#### Chronic Health Effects

See component summary.

No adverse chronic health effects are expected from anticipated conditions of normal use of this material.

#### Conditions Aggravated by Exposure

No additional information is available on whether overexposure to this material would aggravate other existing special medical conditions.

## SECTION 3 : COMPOSITION/INFORMATION ON INGREDIENTS

---

<u>Component Name</u>	<u>CAS #</u>	<u>EU Inventory</u>	<u>Concentration Wt. %</u>
Paraffin	8002-74-2	N/A	20%
Soy Wax	8016-60-2	N/A	80%

## Material Safety Data Sheet

MSDS No.: AHP1703  
Variant: U.S.A.-EN  
Version No: 1.3  
Validation Date: 03/22/2019

# Essentials S3 Core Filled Votive Candles

## SECTION 4: FIRST AID MEASURES

---

### General

Take proper precautions to ensure your own health and safety before attempting rescue and providing first aid. For specific information refer to the Emergency Overview in Section 2 of this MSDS.

### Skin

Remove contaminated clothing as needed. Wash skin thoroughly with mild soap and water. If sticky, use waterless cleaner first. Flush with lukewarm water for 15 minutes.

### Inhalation

Not expected to present a significant inhalation hazard under anticipated conditions of normal use.

### Eye

Immediately flush the eyes with large amounts of clean low-pressure water for at least 15 minutes, occasionally lifting the upper and lower lids. If pain or irritation persists, promptly obtain medical attention.

### Ingestion

Not expected to present a significant ingestion hazard under anticipated conditions of normal use.

### Note to Physician

Treat symptomatically. Treatment of overexposure should be directed at the control of symptoms and the clinical condition of the patient.

## SECTION 5: FIRE FIGHTING MEASURES

---

### Flammable Properties

#### Classification

OSHA/NFPA Class IIIB combustible liquid.

#### Flash Point

~ 70 °C (158 °F) (Open Cup)

#### Auto-Ignition Temperature

No Data Available.

#### Lower Flammable Limit

No Data Available.

#### Upper Flammable Limit

No Data Available.

### Extinguishing Media

#### Suitable:

SMALL FIRE: Use dry chemicals, CO<sub>2</sub>, water spray or alcohol-resistant foam. LARGE FIRE: Use water spray, water fog or alcohol-resistant foam.

#### Unsuitable:

Do not use solid water stream.

### Protection of Firefighters

#### Protective Equipment/Clothing:

Wear positive pressure self-contained breathing apparatus (SCBA). Structural firefighters protective clothing will only

## Material Safety Data Sheet

MSDS No.: AHP1703  
Variant: U.S.A.-EN  
Version No: 1.3  
Validation Date: 03/22/2019

# Essentials S3 Core Filled Votive Candles

### Protective Equipment/Clothing:

provide limited protection.

### Fire Fighting Guidance:

Heat from fire can generate flammable vapor. When mixed with air and exposed to ignition source, vapors can burn in open or explode if confined. Vapors may be heavier than air. May travel long distances along the ground before igniting and flashing back to vapor source. Fine sprays/mists may be combustible at temperatures below normal flash point. Fight fire from a safe distance/protected location. Heat may build enough pressure to rupture closed containers/spreading fire/increasing risk of burns/injuries. Use water spray/fog for cooling. Avoid frothing/steam explosion. Burning liquid may float on water. Although water soluble, may not be practical to extinguish fire by water dilution. Notify authorities immediately if liquid enters sewer/public waters.

### Hazardous Combustion Products:

Thermal decomposition may produce carbon monoxide and other toxic vapors.

## SECTION 6: ACCIDENTAL RELEASE MEASURES

---

### Release Response

Vapors can not ignite. Equip responders with proper protection. Evacuate/limit access. Extinguish all ignition sources. Stop release; prevent flow to sewers/public waters. Notify fire and environmental authorities. Impound/recover large land spill; soak up small spill with inert solids. Use suitable disposal containers. On water, material is soluble and may float or sink. Contain/collect rapidly to minimize dispersion. Disperse residue to reduce aquatic harm. Report per regulatory requirements.

## SECTION 7: HANDLING AND STORAGE

---

### Handling

For industrial use only. When normal handling requires heating, do not heat higher than 28°C/50°F below flash point temperature unless in air-free closed system sealed off from the atmosphere. Handle empty containers with care - residue can burn if heated. Empty containers should be thoroughly rinsed with copious amounts of clean water. The rinse water can be used for makeup water for any necessary dilution of the concentrated product before use, or it can be properly discarded.

### Storage

Keep container tightly closed and properly labeled. Store away from heat/moisture/strong oxidizing agents.

## SECTION 8: EXPOSURE CONTROLS AND PERSONAL PROTECTION

---

### Engineering Controls

No special ventilation is recommended under anticipated conditions of normal use beyond that needed for normal comfort control.

### Personal Protection

#### Inhalation

No special respiratory protection is recommended under anticipated conditions of normal use with adequate ventilation. A respiratory protection program that meets OSHA's 29 CFR 1910.134 or ANSI Z88.2 requirements must be followed whenever workplace conditions warrant respirator use.

#### Skin

Wear chemical resistant gloves such as: Butyl rubber. or Nitrile. Depending on the conditions of use, protective gloves, apron, boots, head and face protection should be worn.

## Material Safety Data Sheet

MSDS No.: AHP1703  
Variant: U.S.A.-EN  
Version No: 1.3  
Validation Date: 03/22/2019

# Essentials S3 Core Filled Votive Candles

### Eye

Eye protection such as chemical splash goggles and/or face shield must be worn when possibility exists for eye contact due to splashing or spraying liquid, airborne particles, or vapor.

### **Additional Remarks**

Selection of appropriate personal protective equipment should be based on an evaluation of the performance characteristics of the protective equipment relative to the task(s) to be performed, conditions present, duration of use, and the hazards and/or potential hazards that may be encountered during use. Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure. Use good personal hygiene practices. Wash hands before eating, drinking, smoking, or using toilet facilities. Promptly remove soiled clothing/wash thoroughly before reuse.

### **Occupational Exposure Limits**

Consult local authorities for acceptable exposure limits.

## **SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES**

---

**Appearance:** Slightly viscous liquid. Clear or light yellow,

**Odor:** Aroma smell

**Odor Threshold:** No value available.

**pH:** Not applicable.

**Boiling Point/Boiling Range:** ~ 228 °C (442.4 °F) @ 760 mm Hg

**Freezing Point/Melting Point:** ~ -40 °C (-40 °F)

**Auto-ignition:** No Data Available.

**Flammability:** OSHA/NFPA Class IIIB combustible liquid.

**Lower Flammable Limit:** No Data Available.

**Upper Flammable Limit:** No Data Available.

**Explosive Properties:** No Data Available.

**Oxidizing Properties:** No Data Available.

**Vapor Pressure:** < 0.1 mm Hg @ 21 °C (69.8 °F)

**Evaporation Rate:** No Data Available.

**Relative Density:** ~ 1.03(Water = 1.0 at 4°C (39.2°F))

**Relative Vapor Density:** ~ 4.6 (Air = 1.0 at 15 - 20°C/59 - 68°F)